

**CALIBRE REPORTS ADDITIONAL STEP OUT AND CONFIRMATORY DRILL INTERCEPTS AT THE PAN
HEAP LEACH GOLD MINE IN NEVADA**

Calibre Mining News Release, April 12, 2022 - Drill Hole Table
See notes at the bottom of the table

Hole	Grade (g/t Au)	Grade (opt Au)	From (m)	To (m)	Length (m)
PR21-031	No Significant Results				
PR21-032	No Significant Results				
PR21-033	0.517	0.015	10.67	18.29	7.62
PR21-034	0.779	0.023	6.10	9.14	3.05
PR21-035	0.477	0.014	0	7.62	7.62
and	0.301	0.009	12.19	22.86	10.67
and	0.369	0.011	67.06	71.63	4.57
PR21-036	0.518	0.015	42.67	47.24	4.57
PR21-037	0.874	0.025	21.34	24.38	3.05
PR21-038	No Significant Results				
PR21-039	0.379	0.011	28.96	39.62	10.67
PR21-040	0.441	0.013	79.25	91.44	12.19
and	0.750	0.022	96.01	121.92	25.91
PR21-041	No Significant Results				
PR21-047	1.016	0.030	141.73	150.88	9.14
includes	1.407	0.041	143.26	147.83	4.57
and	0.338	0.010	158.50	163.07	4.57
and	0.435	0.013	176.78	185.93	9.14
and	0.370	0.011	192.02	195.07	3.05
and	0.213	0.006	207.26	210.31	3.05
PR21-053	1.293	0.038	103.63	121.92	18.29
includes	2.173	0.063	108.20	117.35	9.14
PR21-055	1.458	0.043	64.01	73.15	9.14
includes	2.322	0.068	65.53	70.10	4.57
and	0.633	0.018	76.20	80.77	4.57
and	0.370	0.011	83.82	88.39	4.57
and	0.641	0.019	96.01	103.63	7.62
and	0.697	0.020	106.68	117.35	10.67
and	0.260	0.008	147.83	150.88	3.05
PR21-057	0.272	0.008	10.67	19.81	9.14
and	0.257	0.008	59.44	65.53	6.10
and	0.392	0.011	77.72	97.54	19.81
PR21-058	0.383	0.011	12.19	25.91	13.72
and	0.954	0.028	28.96	44.20	15.24

includes	1.332	0.039	30.48	38.10	7.62
PR21-060	No Significant Results				
PR22-001	No Significant Results				
PR22-002	0.393	0.011	10.67	18.29	7.62
PR22-003	0.313	0.009	0	4.57	4.57
and	0.268	0.008	15.24	18.29	3.05
PR22-004	0.448	0.013	4.57	18.29	13.72
PR22-005	0.586	0.017	0	4.57	4.57
PR22-006	No Significant Results				
PR22-007	0.492	0.014	111.25	115.82	4.57
PR22-008	No Significant Results				
PR22-019	No Significant Results				
PR22-021	No Significant Results				
PR22-022	No Significant Results				
PR22-023	0.327	0.010	53.34	57.91	4.57
PR22-024	No Significant Results				
PR22-025	0.320	0.009	51.82	59.44	7.62

Notes: All holes were drilled at angles of -45 to -90 degrees at azimuths designed to intersect targeted structures as nearly as possible to perpendicular when possible. Some drill holes and intercepts reported on here did not cross mineralization perpendicularly, and do not represent exact 'true widths'. These instances are illustrated in the sections provided. The Company conducts a significant QA/QC program which includes the insertion of assay standards, blanks, and duplicates in the sample stream to ensure the assay lab results are within specified performance levels. Down hole deviation surveys are provided by International Directional Services, utilizing a surface recording gyroscope, and by trained drill crews operating a north seeking gyroscope supplied by REFLEX.